

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (previously presented) A device for transmitting torque between two rotatable, coaxial shaft members, the device containing

 a clutch between the two shaft members and engageable to counteract rotational speed differential between the shaft members by means of a hydraulic piston under the control of an electrically controlled throttle or pressure valve,

 and a clutch pump for supplying hydraulic pressure to the hydraulic piston, wherein the clutch pump is a differential pump driven by the rotational speed differential between the two shaft members,

 wherein the hydraulic piston, the valve, and the clutch pump are connected in a hydraulic system also containing a feeder pump for maintaining a certain base pressure in the system,

 characterized by means in the hydraulic system for conditionally allowing flow from the feeder pump past the valve to the hydraulic piston irrespective of the flow from the clutch pump.

2. (cancelled)

3. (withdrawn and currently amended) A device according to claim 2 1,

 in which the hydraulic system in a closed portion comprises lines from the differential pump, through the electrically controlled throttle or pressure valve to the clutch, the portion including check-valves, and in which oil may be supplied by the feeder pump from a reservoir and may be removed to the reservoir via an overflow valve,

wherein the feeder pump and the differential pump are connected in series by means of a check-valve between the overflow valve and the feeder pump.

4. (withdrawn) A device according to claim 3, wherein an accumulator is arranged in connection with the overflow valve.

5. (withdrawn) A device according to claim 3, wherein an accumulator is arranged in connection with the feeder pump.

6. (currently amended) A device according to claim 1,

~~in which the hydraulic system in a closed portion comprises lines from the differential pump, through the electrically controlled throttle or pressure valve to the clutch, the portion including check valves, and in which oil may be supplied by the feeder pump from a reservoir and may be removed to the reservoir via an overflow valve,~~

wherein the feeder pump and the differential pump are connected in parallel by means of a check-valve between the feeder pump and the electrically controlled throttle or pressure valve.

7. (previously presented) A device according to claim 6, wherein an overflow valve is connected in parallel over the check-valve.

8. (withdrawn) A device according to claim 7, wherein a pressure transducer is arranged in conjunction with the electrically controlled throttle or pressure valve.